APPENDIX 9-4: HYDROLOGY AND HYDROGEOLOGY 9

Appendix 9-4: Greenfield Runoff Modelling

APPENDIX 9-4: HYDROLOGY AND HYDROGEOLOGY 9

REFH2 Greenfield Runoff Rates

Return period (yrs)	As-rural peak flow (m^3/s)	As-rural peak flow (I/s)
1	0.0196	19.6
2	0.0228	22.8
5	0.0338	33.8
10	0.0426	42.6
30	0.0598	59.8
50	0.0705	70.5
75	0.0807	80.7
100	0.0891	89.1
200	0.1123	112.3
1000	0.1756	175.6

APPENDIX 9-4: HYDROLOGY AND HYDROGEOLOGY 9



estimation for sites

			www.uksuds.co	m Greenfield runoff too
Calculated by:	Henry Lister		Site Details	
Site name:	Stanninghall		Latitude:	52.71662° N
Site location:	Horstead		Longitude:	1.34374° E
his is an estimation o	f the greenfield runoff rate	es that are used to meet normal best		
or developments", SC	030219 (2013), the SuDS	guidance "Rainfall runoff management 6 Manual C753 (Ciria, 2015) and	Reference:	2523407665
ne non-statutory stand e	dards for SuDS (Defra, 20	15). This information on greenfield runoff rate	s may Date:	Jun 24 2020 11:34
ne basis for setting co	nsents for the drainage of	f surface water runoff from sites.		
Runoff estimat	ion approach	FEH Statistical		

Notes Site characteristics Total site area (ha):

43.65

Methodology

 $Q_{\mbox{\scriptsize MED}}$ estimation method: Calculate from BFI and SAAR BFI and SPR method: Specify BFI manually HOST class: N/A BFI / BFIHOST: 0.861 Q_{MED} (I/s): Q_{BAR} / Q_{MED} factor:

1.12

SAAR (mm): Hydrological region: Growth curve factor 1 year: Growth curve factor 30 years: Growth curve factor 100 years: Growth curve factor 200 years:

Hydrological characteristics

Default	Edited	
619	619	
5	5	
0.87	0.87	
2.45	2.45	
3.56	3.56	
4.21	4.21	

(1) Is Q_{BAR} < 2.0 l/s/ha?

When Q_{BAR} is < 2.0 l/s/ha then limiting discharge rates are set at

(2) Are flow rates < 5.0 l/s?

Where flow rates are less than 5.0 l/s consent for discharge is usually set at 5.0 Vs if blockage from vegetation and other materials is possible. Lower consent flow rates may be set where the blockage risk is addressed by using appropriate drainage elements.

(3) Is SPR/SPRHOST ≤ 0.3?

Where groundwater levels are low enough the use of soakaways to avoid discharge offsite would normally be preferred for disposal of surface water runoff.

Greenfield runoff rates		
	Default	Edited
Q _{BAR} (I/s):		22.35
1 in 1 year (l/s):		19.44
1 in 30 years (l/s):		54.76
1 in 100 year (I/s):		79.57
1 in 200 years (I/s):		94.1

This report was produced using the greenfield runoff tool developed by HR Wallingford and available at www.uksuds.com. The use of this tool is subject to the UK SuDS terms and conditions and licence agreement, which can both be found at www.uksuds.com/terms-and-conditions.htm. The outputs from this tool are estimates of greenfield runoff rates. The use of these results is the responsibility of the users of this tool. No liability will be accepted by HR Wallingford, the Environment Agency, CEH, Hydrosolutions or any other organisation for the use of this data in the design or operational characteristics of any drainage scheme.